"SINGLE SECTION" Industrial Alloy Ladders



SINGLE SECTION Alloy Ladders - round rungs Made to BS2037 Class1 Industrial Duty - not kitemarked						
Code	Closed Height	Rung Type	No Rungs	Weight		
CLS1010	1.00m / 3' 3"	Round	4	1.5		
CLS1012	1.25m / 4' 1"	Round	5	1.9		
CLS1015	1.50m / 4' 11"	Round	6	2.3		
CLS1017	1.75m / 5' 9"	Round	7	2.7		
CLS1020	2.00m / 6' 6"	Round	8	3.1		
CLS1022	2.25m / 7' 4"	Round	9	3.4		

SINGLE SECTION Alloy Ladders - round rungs Made to BS2037 Class1 Industrial Duty - not kitemarked						
Code	Closed Height	Rung Type	No Rungs	Weight		
RGS115	1.55m / 5' 1"	Round	6	3.0		
RGS120	2.05m / 6' 9"	Round	8	4.0		
RGS125	2.55m / 8' 4"	Round	10	5.0		
RGS130	3.05m / 10' 0"	Round	12	6.0		
RGS135	3.55m / 11' 8"	Round	14	7.0		
RGS140	4.05m / 13' 4"	Round	16	8.0		
RGS145	4.55m / 14' 11"	Round	18	9.0		
RGS150	5.05m / 16' 7"	Round	20	12.0		
RGS155	5.55m / 18' 3"	Round	22	16.0		
RGS160	6.05m / 19' 10"	Round	24	18.0		
RGS170	7.05m / 23' 2"	Round	28	20.0		

- SINGLE Section Alloy Ladders to BS Class 1 for a variety of specialist applications around the workplace.
- These Heavy Duty "Class 1 Industrial" ladders are designed for years of rigorous service.
- All are made to the strongest Industrial Duty BS2307 Class 1 with a Maximum Safe Load 175kg (27.5stones). Duty rating 130kg (20.5stones). BS2037 is now withdrawn so none are kitemarked but all are still made to that same strength & durability standard.
- Side stiles are of box-section alloy which is graded in size according to the ladder length. Solid moulded rubber bungs fitted at top and bottom.
- Our CLS range has 25mm diameter alloy Round Rungs which are heavily ribbed for non-slip safety.
- represent an economical solution to many access problems. These are suitable for all uses whether used vertically or at any other angle because footing angles remain the same in all cases. Overall width 330mm. Rung Spacing 250mm.
- Our RGS range has 25mm diameter alloy Round Rungs which are heavily ribbed for non-slip safety. These are suitable for all uses whether used vertically or at any other angle because footing angles remain the same in all cases. Overall width 325mm. Rung Spacing 250mm.
- Specials with bespoke modifications are optional for RGS range.

See our excellent website at

www.ladders999.co.uk

for prices of these and our huge range of ladders, steps, podium steps and scaffold towers

UNITS 2 & 10 CHANCEL CLOSE TRADING ESTATE
EASTERN AVENUE **GLOUCESTER** GL4 3SN
FAX: 01452 505580

TEL: 01452 520144

www.ladders999.co.uk sales@lansfordaccess.co.uk

All prices, details and specifications are subject to change without notice and are those ruling at date of order. E&OE.

"SINGLE SECTION" Industrial Alloy Ladders





See our excellent website at

www.ladders999.co.uk

for prices of these and our huge range of ladders, steps, podium steps and scaffold towers

UNITS 2 & 10 CHANCEL CLOSE TRADING ESTATE EASTERN AVENUE **GLOUCESTER** GL4 3SN

FAX: 01452 505580

TEL: 01452 520144

www.ladders999.co.uk sales@lansfordaccess.co.uk

All prices, details and specifications are subject to change without notice and are those ruling at date of order. E&OE.